



河海动力  
HEHAI POWER



## 燃(沼)气发电机组 (BIO)GAS ENGINE GENERATOR

南通河海动力设备有限公司  
NANTONG HEHAI POWER EQUIPMENTS CO.,LTD.



南通河海动力设备有限公司是专业生产10~500kW沼气发电机组、天燃气发电机组等系列产品的高新企业。公司生产的沼气发电机组、天燃气发电机组所使用的发动机是本公司专利产品；发电机采用斯坦福、西门子、美奥迪等名优产品。发电机组经公司专业工程师的精心测试，具有调压精度高、动态性好，电压波形畸变小及工作可靠、效率高等特性。公司生产的燃气发动机及配套的燃气发电机组、沼气发电机组已有十多年研究经验，其主要技术参数已达到柴油发电机组水平，可采用的气体有：管道天然气、石油伴生气、焦化气、煤层气、垃圾填埋及养殖场的各种沼气、甲醇气等，具有环保、安全、效率高等特点。

公司现有技术开发工程师21人，产品开发实力雄厚；公司测试设备和测试技术已处国内同行业前沿，拥有国内先进的全电脑、大功率、多台位的测试设备，能同时检测4台发电机组，测试功率达2000kW。

公司生产的沼气发电机组、天燃气发电机组已广泛在江苏、广东、安徽、陕西、贵州、河南、甘肃、新疆、台北、孟加拉国、泰国等省份和国家的养殖场、畜牧场、井场等相关行业使用，并在国内设立了多个产品售后服务处，有经过严格培训的专职服务人员负责售后服务。



# 南通河海动力设备有限公司

NANTONG HEHAI POWER EQUIPMENTS CO.,LTD.

Nantong Hehai Power Equipments Co., Ltd. is a high-new technological enterprise, which is specialized in manufacturing biogas generating set and natural gas generating set with power range from 10kW to 500kW. The engine, used in gas generating set is patented product owned by our company. The generator is adopted with famous brand such as Stanford, Siemens and Meaodi etc. After the generating set has been completely adjusted by our professional technician, it has the features of high voltage-regulating precision, better dynamic performance, low voltage wave distortion rate, high efficiency, reliable operation, friendly environment and safety etc. As our company has produced the gas engine and gas generating set for more than ten years, we have accumulated rich experience in development and production. The main technical data has been up to the level of diesel generating set. The following gases can be used for generating set: piping natural gas, petroleum-associated gas, coking gas, coal bed gas, marsh and methanol gas etc.


Our company has strong technical forces with 21 technical engineers for product development, and takes the lead domestically in measurement equipment and its technology with computer-controlled & big power & many tested benches. It can test 4 sets of the generating sets with 2000kW maximum power at the same time.

The biogas generating set and natural gas generating set, produced by our company, have been sold to many provinces in China such as Jiangsu, Guangdong, Anhui, Shanxi, Guizhou, Henan, Gansu, Xinjiang and Taiwan, and exported to Bangladesh, Thailand. The product is widely used in breeding farm, livestock farm and well site etc. Many after-sale service centers have been set up with profession servicemen and quick response.





河海动力  
HEHAI POWER



## 技术参数 Technical parameters

机组型号 Model of the generating set	机组功率 Power of the generating set kW	发动机型号 Model of the engine	额定转速 Rated speed r/min	外形尺寸 Overall dimensions mm	重量 Weight Kg
20GFT48	20	2135T	1500	2100×760×1350	1000
24GFT49	24	2135T	1500	2100×760×1350	1000
30GFT50	30	2135AT	1500	2100×760×1350	1050

备注：1、机组采用电马达启动、电子调速、闭式循环（两种冷却方式：风、水冷却方式；水、水冷却方式）；  
2、沼气进气压力为0.2MPa，甲烷含量≥50%（体积百分比），总硫含量≤460mg/m<sup>3</sup>，硫化氢含量≤20mg/m<sup>3</sup>，沼气中不得含游离水与油；  
3、发电机组发电参数：频率：50Hz；电压：400/230V；功率因数：0.8



### 技术参数 Technical parameters

机组型号 Model of the generating set	机组功率 Power of the generating set kW	发动机型号 Model of the engine	额定转速 Rated speed r/min	外形尺寸 Overall dimensions mm	重量 Weight Kg
40GFT51	40	4135T	1500	2250×900×1550	1350
45GFT51	45	4135T	1500	2250×900×1550	1350
50GFT52	50	4135AT	1500	2250×900×1550	1450
55GFT52	55	4135AT	1500	2250×900×1550	1450
60GFT53	60	4135AT-2	1500	2350×900×1550	1550

Remark: 1. The generating set: starting with electric motor, electronically speed-regulating, closed circulation (two kinds of cooling way: wind / water cooling and water / water cooling);  
 2. Inlet pressure of biogas: 0.2MPa, Content of Methane: ≥50% (volume percent), Content of total sulfur: ≤460mg/m<sup>3</sup>, Content of hydrogen sulphide: ≤20mg/m<sup>3</sup>, No free water and free oil in biogas;  
 3. Generating data of the generating set: Frequency: 50Hz, Voltage: 400/230V, Power factor: 0.8




河海动力  
HEHAI POWER



### 技术参数 Technical parameters

机组型号 Model of the generating set	机组功率 Power of the generating set kW	发动机型号 Model of the engine	额定转速 Rated speed r/min	外形尺寸 Overall dimensions mm	重量 Weight Kg
64GFT22	64	6135T-1	1500	2502×1000×1550	2000
75GFT60	75	6135T-2	1500	2550×1000×1800	2010
82GFT60	82	6135T-2	1500	2550×1000×1800	2010
90GFT32	90	6135AT-1	1500	2700×1000×1800	2250
100GFT35	100	6135AT-2	1500	2700×1000×1800	2300
120GFT54	120	6135RT	1500	2910×1000×1800	2450
120GFT57	120	6135DRT	1500	2930×1000×1800	2450

备注：1、机组采用电马达启动、电子调速、闭式循环（两种冷却方式：风、水冷却方式；水、水冷却方式）；  
2、沼气进气压力为0.2MPa，甲烷含量≥50%（体积百分比），总硫含量≤460mg/m<sup>3</sup>，硫化氢含量≤20mg/m<sup>3</sup>，沼气中不得含游离水与油；  
3、发电机组发电参数：频率：50Hz；电压：400/230V；功率因数：0.8



### 技术参数 Technical parameters

机组型号 Model of the generating set	机组功率 Power of the generating set kW	发动机型号 Model of the engine	额定转速 Rated speed r/min	外形尺寸 Overall dimensions mm	重量 Weight Kg
150GFT57	150	12V135T	1500	3400×1350×1850	3500
160GFT57	160	12V135T	1500	3500×1350×1850	3550
180GFT58	180	12V135AT	1500	3550×1350×1850	3550
200GFT59	200	12V135AT	1500	3570×1350×1850	3600
250GFT61	250	12V138RT	1500	3700×1350×1900	3800

Remark: 1. The generating set: starting with electric motor, electronically speed-regulating, closed circulation (two kinds of cooling way: wind / water cooling and water / water cooling);  
 2. Inlet pressure of biogas: 0.2MPa, Content of Methane: ≥50% (volume percent), Content of total sulfur: ≤460mg/m<sup>3</sup>, Content of hydrogen sulphide: ≤20mg/m<sup>3</sup>, No free water and free oil in biogas;  
 3. Generating data of the generating set: Frequency: 50Hz, Voltage: 400/230V, Power factor: 0.8




## 技术参数 Technical parameters

机组型号 <b>Model of the generating set</b>	机组功率 <b>Power of the generating set</b> kW	发动机型号 <b>Model of the engine</b>	额定转速 <b>Rated speed</b> r/min	箱体尺寸 <b>Packing dimensions</b> mm	重量 <b>Weight</b> Kg
X250GFT61	250	12V138RT	1500	6000×2500×2500	7000
X250GFT60	250	12V138RUT	1500	6000×2500×2500	7000

备注：1、机组采用电马达启动、电子调速、闭式循环（两种冷却方式：风、水冷却方式；水、水冷却方式）；  
 2、沼气进气压力为0.2MPa，甲烷含量≥50%（体积百分比），总硫含量≤460mg/m<sup>3</sup>，硫化氢含量≤20mg/m<sup>3</sup>，沼气中不得含游离水与油；  
 3、发电机组发电参数：频率：50Hz；电压：400/230V；功率因数：0.8

Remark: 1. The generating set: starting with electric motor, electronically speed-regulating, closed circulation (two kinds of cooling way: wind / water cooling and water / water cooling) ;  
 2. Inlet pressure of biogas: 0.2MPa, Content of Methane: ≥50% (volume percent), Content of total sulfur: ≤460mg/m<sup>3</sup>, Content of hydrogen sulphide: ≤20mg/m<sup>3</sup>, No free water and free oil in biogas ;  
 3. Generating data of the generating set: Frequency: 50Hz, Voltage: 400/230V, Power factor: 0.8

## 配套产品 Matched Products



压缩机组  
Compressor set



余热利用发生器  
Afterheat utilizing generator



水气分离罐  
Water-gas separating can



阻火器  
Flame arrester



脱硫系统  
Desulphurization system



储气稳压罐  
Gas-stored steady voltage can



脱硫罐  
Desulphurization can



冷却水箱  
Cooling water tank






河海动力  
HEHAI POWER

## 沼气发电机组安装示意图

Installation schematic diagram of biogas generating set



说明：从储气稳压罐往前各设备底部均有排污阀门，安装过程中请预先做好排污排水渠道。

Remark: There are drainage valves on the bottom of all equipments before gas-stored steady voltage can. The work for sewage drainage channels should be completed prior to installation.

## 部分工程 Projects List



## 部分客户 Customers List

江苏正大苏垦猪业有限公司 姜堰市沪江畜业有限公司 南京绿康种猪有限公司 苏州哥弟畜禽有限公司 江苏国明农业开发有限公司 江苏高邮巧妹子科技养殖园 江苏申川畜牧有限公司 宜兴市昌兴生态农业有限公司 三和羚杰牧业有限公司 南京世纪开源实业有限公司 南京奎奎黑猪养殖专业合作社 南京晟泰沅农牧发展有限公司 常州康乐农牧有限公司 南京市汤泉农场 苏州市太湖牧业有限公司 无锡唯琼农业生态园 太仓市金诸种猪场 太仓市种猪厂 金坛市肠衣厂 海门市南海种猪场 南通华多种猪繁育有限公司 长寿集团江安联络猪场 张家港枫华种猪场 江苏正大农垦 浙江天善食品公司 临安市於潜镇文华农牧公司 味全乳品专业牧场有限公司 嘉兴南湖区正宇猪厂 南浔菱湖精鑫生猪饲养场 浙江绿谷牧业有限公司 金华市金东区大堰河农牧 浙江萧山江南养殖有限公司 杭州萧山钱江出口养殖实业有限公司 宁波久久红农业发展有限公司 浙江绍兴中大畜牧有限公司 浙江温岭泽国镇天星猪场 杭州萧山康盛养殖有限公司 浙江文成新伟畜牧养殖有限公司 杭州康盛农牧养殖 湖南大康牧业股份有限公司 祁东县兴隆土畜产品有限公司 莆阳市兴养殖专业合作社 湖南正大畜禽有限公司 上海市东方种蓄场有限公司 上海农场下明畜牧场 上海浦东机械设备有限公司	上海丰海种猪繁育有限公司 安徽长风农牧科技有限公司 池州大阳生态农业有限公司 池州市三鑫生猪养殖专业合作社 安徽绿健种猪有限公司 安徽曦强乳业集团乳牛厂 安徽省滁州市达诺乳业万牛园牧场区 凤阳县族光生态养殖有限公司 湖北金旭农业发展股份有限公司 襄樊农牧食品有限公司 宜昌正大食品有限公司 武汉中粮肉食品有限公司 宜昌正大畜牧有限公司 湖北黄石健丰牧业有限公司 湖北浠水长流牧业有限公司 湖北龙王畜牧有限公司 河南谊发牧业有限公司 河南郑州巩义牛师兄 河南郑州新郑雏鹰集团 河南省中牟县郑中畜牧有限公司 河南省新大牧业有限公司 洛阳盛平生态科技有限公司 高阳县科农猪业有限公司 保定市远方农牧有限公司 曲阳县六马种猪养殖有限公司 霸州市利华燃气储运有限公司 安康市汉滨区阳晨牧业科技有限公司 中央延安党校 铜川哼瑞种猪厂 西安蓝天石化设备有限公司 陕西兴平市星光良种猪场繁育公司 宁夏汇达能源环境工程有限公司 甘肃云发商贸有限公司 甘肃康美现代农牧产业集团有限公司 临洮兴达乳业有限责任公司 天水陇丰养殖有限责任公司 杭州普达可再生能源设备有限公司(甘肃临泽雪莲乳品) 贵州省荔波县永康乡军华畜牧发展有限公司 贵阳市乌当区新场乡大兴奶牛厂 贵阳修文县好一多奶牛厂 贵阳修文县龙山乳业有限公司 贵州黔林州环保能源科技有限公司 贵州凉都鑫农牧业有限公司 贵州雷格农牧 四川省凉山洲会理县德林养殖场 射洪县超强肉食品公司	四川省天兆畜牧科技有限公司 瑞安市鑫农畜禽专业合作社 重庆隆生农业发展有限公司原种猪厂 渝西畜科城 云南省曲靖市宣威海璇实业有限公司 黑龙江省佳木斯市联喜畜牧有限公司 佳木斯联畜牧发展有限公司 大庆佳明养殖有限公司 牡丹江大湾牧业有限公司 新疆信天翁环保能源科技公司 哈密市伊吾县鑫祥生猪养殖专业合作社 新疆阿克苏农一师8团 新疆阿克苏拜城县富康猪业场 沈阳坤鑫种猪厂 总装备部辽河种猪场 辽宁沈阳市林盛生态养殖场 广东湛江农垦畜牧有限公司 泊罗高粱宏猪场 广东英德市德丰农牧发展有限公司 广东东江畜牧有限公司 广东宝兴农牧科技有限公司 广东中人环保科技工程有限公司 梅州市恒星畜牧实业有限公司 惠州市泉新畜牧业有限公司 博罗县马石岗猪场 博罗丰润畜牧有限公司 博罗园洲佛岭猪场 惠州市长宁镇邓达明猪场 惠州市罗兴牧业有限公司 惠州市黄田畜牧有限公司 博罗县泰美畜牧有限公司 阳江市宝山富兴牧业有限公司 河源市玉井猪场 广东端昌食品进出口公司致富猪场 广东揭东县玉泉有机农业开发有限公司 广东省连平湖东农牧实业有限公司 广东省连平广南猪场 内蒙准格尔旗传祥垃圾处理有限公司 内蒙乌海垃圾处理有限公司 鄂尔多斯市乌审旗翔云再生资源开发责任有限公司 北京盈和瑞环保设备有限公司(太湖水葫芦) 广西扬翔猪基因科技有限公司 广西必佳生物环保能源有限公司 广西扬翔农牧有限责任公司 宁夏瑞威尔能源环境工程有限公司 超马电机股份有限公司(台湾)
---	--	---

说明：我公司的客户工程约1200余家，以上为部分工程展示，排名不分先后。

Remark: We have about 1200 customers. The above is only demonstration for partial construction. The company name listed is in no particular order.

声明：由于不断的发展，实际值/技术参数可能与现在样本中提到的不同。

Note: Due to continuous development, actual limits/technical parameters may differ from those mentioned in this list.



# 南通河海动力设备有限公司

NANTONG HEHAI POWER EQUIPMENTS CO.,LTD.

公司地址：江苏省南通市越江路89号 邮编：226005

Add: No.89 Yuejiang Road, Nantong City, Jiangsu,China P.C.: 226005

电话(Tel): +86-513-85606135 85605391

传真(Fax): +86-513-85601599

网址(Web Site): <http://www.nthhdl.cn>

E-mail: nthhdl@126.com